

FAST CHARGING

## NRG 80 A (19.2 kW) – LEVEL 2 AC CHARGER



### KEY FEATURES

**11x faster than normal wall outlet**  
Minimize wait time

**80 A continuous output**  
Safe, reliable charging

**2.9-in OLED display**  
Easy and intuitive

**Customization options**  
Build your brand

### EASY TO INSTALL – WALL OR PEDESTAL MOUNT

### PERFECT FOR



SINGLE FAMILY  
HOMES



MULTIFAMILY &  
COMMERCIAL



PARKING LOTS



SERVICE STATIONS &  
CHARGE POINTS



HEALTHCARE &  
HOSPITALITY

**FOR MORE INFORMATION  
OR TO PLACE AN ORDER**

JASON BROWN

 +1-801-554-4648

 [info@energispot.com](mailto:info@energispot.com)

 [www.energispot.com](http://www.energispot.com)

FAST CHARGING

# NRG 80A (19.2 kW) - LEVEL 2 AC CHARGER



WALL MOUNT



PEDESTAL MOUNT

## Technical Specifications

DESCRIPTION		NRG 80 A
Input	Voltage	200-240 VAC, Single phase
	Connection	L+G+N
	Frequency	50 Hz / 60 Hz
	Current	80A
Output	Current	80A
	Power	19.2 kW continuous output
	Connector	SAE-J1772 Type 1
	Charging gun length	16 feet
Environment	Operating temperature	-25°C - 50°C (-13°F - 122°F)
	Storage temperature	-30°C - 70°C (-22°F - 158°F)
	Altitude	≤ 6,652 feet
	Humidity	<95% (non-condensing)
Mechanical	Dimensions	285mm (W) x 190 mm (D) x 402 mm (H)
	Weight	8 kg (17.6 lbs) - unit, cord, connector
	Ingress Protection	NEMA 3R
Cooling		Natural cooling
Network & Protocol		Ethernet / OCPP 1.6J
Display		2.9 inch OLED
User Authentication		RFID (standard) / App (optional with MSP)
Push Button		Emergency stop
Protection		Over voltage / Under voltage / Over current Insulation / Over temperature / Surge / Residential current / Ground fault / Welding