


EXPRESS CHARGING

NRG 180 - DC SUPER FAST CHARGER



KEY FEATURES

Single or dual port charging

Tailor service level to your business

16-in touchscreen

Easy and intuitive

Up to 180 kW Output

Charge and go

Customization available

Build your brand

ORDER TO DELIVERY IN <12 WEEKS



AUTOMOTIVE
DEALERSHIPS



PARKING LOTS

PERFECT FOR



SERVICE STATIONS &
CHARGE POINTS



MULTIFAMILY &
COMMERCIAL



FLEETS

FOR MORE INFORMATION OR TO PLACE AN ORDER

JASON BROWN


 +1-801-554-4648

 jason@energispot.com

 www.energispot.com

EXPRESS CHARGING

NRG 180 – DC SUPER FAST CHARGER



Technical Specifications

DESCRIPTION		NRG-180 DC SUPER FAST CHARGER
Input	Input Voltage	480VAC, 3P+N+PE (Wye configuration)
	Frequency	50 / 60 Hz
	Efficiency	>95% (Full load)
Output	Output Voltage	200-950 VDC
	Output Current	300A
	Power	180 kW (max single port) / 90 kW (max dual port)
	Connector	US & Canada CCS1 180 kW (standard) / NACS (optional)
User Interface	Display	16-inch LCD with touchscreen
	Push Buttons	Emergency Stop
	User Authentication	OCPP 1.6J (up to 2.0) / RFID card reader
Network Connection		Ethernet (standard) / 4G Dual Carrier (optional)
Environmental	Operating Temperature	-30°C to 50°C (-22°F to 122°F)
	Storage Temperature	-30°C to 70°C (-22°F to 158°F)
	Humidity	<95% (non-condensing)
	Altitude	<8,200 feet
	Ingress Protection	Cabinet / Terminal NEMA 3R (IP55)
	Enclosure Protection	IK10 (Screen not included)
	Cooling	Forced Air
Mechanical	Dimensions (W x D x H)	Cabinet: 1400mm x 900mm x 1900mm Terminal: 527[800]mm x 414[590]mm x 1763.5mm
	Weight	Cabinet: <750kg (1650 lb) Terminal: <200 kg (440 lb)
	Cable Length	18 feet (standard) / Cable retracting kit (optional)
Protection		Over voltage / Under voltage / Over current Over temperature / Surge / Residual current
Compliance		UL 2022, UL 2231-1/-2, FCC part 15B